

AXIUM DX4000

Exceeding expectations at the counter



- Ensure business continuity with battery backup
- Top-level security with Android & PCI PTS V6 compliancy
- Supported by Ingenico Services for an optimized efficiency in estate and security management





Whether accept payments at counter or focus on more advanced capabilities, the AXIUM DX4000 makes it possible.

The power of Android 10. Harness the power of the Appstore.

Maximized network availability

- Wi-Fi and Bluetooth
- Optional Ethernet through MagicBox
- Battery back-up to cover power loss

Seamless integration at counter

- All-in-one compact device
- Optional MagicBox offering various wired connectivity

Raising the bar on security with PCI PTS v6 and Ingenico security tools

Integrated printer and optional camera

Optimized checkout time

- EMV Chip & PIN, contactless, magstripe or digital wallets
- Large 5" color touch display and highlighted contactless zone provide an engaging payment experience
- Highlighted contactless zone

Fully outsourcing of terminal's life cycle management with TaaS package

Specifications

OS	Android	Android 10 Security OS	~
Memory	InternalExternal	 16GB Flash 2GB RAM MicroSD Card slot 	~ ~
Processor	 Application processor Crypto processor 	 64-bit ARM, Cortex Quad-core A53, 1.3GHz 32-bit ARM, security core SC300, 192MHz 	~
Card readers	 Magnetic card reader Smart card reader NFC/ contactless 	 Support ISO 1/2/3 track data, bi-directional swiping EMV L1 and ISO7816 spec compliant EMV Contactless L1 3.1 spec compliant; support ISO / IEC 14443 Type A / B 	* * *
SAM slots	• 3 slots	• 3 SAM	~
Display	 Color / capacitive multi-touch 	• 5" HD, 1280 x 720 px	~
Printer	 Integrated thermal printer 	• Diameter: 40mm	~
Keys & Keypad	 Power key & volumes keys Capacitive screen keys 	 1 Power key & 2 volumes keys Physical screen keys: Menu, Home, Back 	~

Audio	 Speaker 	 Internal speaker 	~
	 Buzzer 	 Internal buzzer 	~
	 Microphone 	 Internal microphone 	Option
Connectivity	• LAN	Bluetooth 4.2 support low	~
		energy • WiFi IEEE8.2.11 a/b/g/n/ac, 2.4GHz and 5GHz	~
		 Ethernet 10/100" 	~
Connections	• USB	• USB Type C	~
Data capture	Positioning	 Tracking GPS, GLONASS, BEIDOU 	~
	 Front facing camera 	 0.3MP, fixed focus, code scanning 	Option
Battery	• Li-ion	 2200mAh / 7.2V, 15.8Wh (equal to 4270mAh / 3.7V) 	~
MagicBox	Ports	Ethernet, USB Host, USB device, USB C	Option
Size	Terminal only	• 6.63 x 3.15 x 2.15'' (177.6 x 80 x 56.8 mm)	~
Weight	 Terminal + battery 	• 15.34oz (435g)	~
Security	PCI PTS V6		~
Environment	 Operating Temperature 	 14°F to 122°F (-10°C to +50°C) 	~
	 Storage 	 -4°F to 158°F (-20°C to +70°C) 	~
	Temperature • Operating Humidity	 (-20 C to +/0 C) 10% to 90% non-condensing 	~



UCP Inc. www.ucp-inc.com Tel.702-802-3504 Email. info@ucp-inc.com

ł.

7200 W Post Rd Suite 100, Las Vegas, NV, 89113

